

2001 E37 Elite Security Shutter

Applications

High security domestic and commercial sites. The E37 Elite is insurance approved, and included in the Secured by Design scheme. Tested according to LPS1175 (6.0), with a Security Rating (SR) of 1, the E37 Elite has been designed for external and internal window apertures and can be fitted to door openings with a maximum structural opening width of 3m (9m² area overall).

Since the stability of the shutter contributes to the security rating, the shutter must only be fixed to approved substrates. It may be fitted internally or externally to: brick, block, aluminium box section, or steel box section.

Curtain Slat

Double-skinned extruded aluminium with security end-locks and, on an external fix, guide bullet locks. Standard Colours: The extruded E37 profile can be powder coated any colour as standard.

Blind Surface:	37mm
Weight per m ² :	7.3kg
Max width:	3000mm
Max surface:	9m ²

Enclosure

The enclosure is manufactured from extruded aluminium with a powder-coated finish (roll-formed aluminium enclosure on internal fix). End caps are pressure moulded aluminium alloy. Standard colours: all BS / RAL colours available as standard.

Shutter Height (mm)	Box Size (mm)
1000	138
1200	150
1700	165
2000	180
2900	205
3800	250
4000	300

Guide Channels / Bottom Slat

Heavy duty guides and bottom slats from extruded aluminium, powder coated any RAL / BS colour as standard.

Operation

Electric: Single phase tubular motor & remote external key-switch as standard. Numerous options such as group or remote control etc. Manual override facility as required.

