

2055 S100 Insulated Security Shutter

Applications
High security commercial sites requiring large aperture coverage and improved insulation properties from the shutter.

Curtain Slat
Double skinned 100mm slat with polyurethane foam insulating core. Perspex windows can be incorporated as required.
Standard galvanised finish.
Colour finishes available on request. Plastisol range, or any BS / RAL colour in polyester powder coated finish.

Profile Height	100mm
Weight per m ²	16.5kg
Maximum Width	12,000mm
Maximum Surface	50m ²

Enclosure
Manufactured from 0.7mm or 0.9mm galvanised steel sheet.
End caps are fabricated from 3mm steel.
Standard galvanised finish. Other colours available on request.

Shutter Height (mm)	Box Size (mm)
3000	400
4000	450
4500	510

Note: The above enclosure sizes are based on standard 3-phase motor operation.

Guide Channels / Bottom Slat
Galvanised steel bottom slat with EPDM weather seal.
Guide channel depth is 85mm as standard.
Standard galvanised finish: Other colours available on request.
The guide channels are bolted to fixing angles or box section to suit the application, as shown on the drawing (right).

Operation
Electric: Single phase tubular motor or 3-phase outboard motor (dependent on curtain weight) with push button control.
Numerous control options such as group or remote control etc., available as required. Manual override facility as required.

CE compliant to all applicable directives and regulations.

