

2055 T77 Security Shutter

Applications

Medium security domestic & low to medium security commercial sites, up to 16m². The T77 can be upgraded to a remote controlled garage door and, further, to 'Secured by Design' status - LPS 1175 SR1 (see T77 Classic Garage Door, and T77 Elite Garage Door).

Curtain Slat

Aluminium double-skinned polyester powder coated slat with polyurethane foam insulating core.
Standard colours: white, brown, beige, blue, red, green, yellow, black, light grey, metallic silver, anthracite grey, wood effect

Blind Surface:	77mm
Weight per m²:	5.5kg
Maximum Width:	5500mm
Maximum Surface:	16m²

Enclosure

Manufactured from roll-formed aluminium with a stove-enamelled finish.
End caps are pressure-moulded aluminium alloy.

Shutter Height (mm)	Box Size (mm)
2000	250
3000	300
4000	360

Guide Channels / Bottom Slat

Bottom slat from extruded aluminium with EPDM weather seal.
Guide channels with brush infill and a depth of 90mm, 70mm or 150mm.
Standard guide channel colours: White or Brown. Other colours available on request.

Operation

Electric: Single phase tubular motor & wall switch as standard.
Numerous options such as group or remote control etc. Manual override facility as required.

Note: Manual operation is available but not common for the T77 profile as it is utilised for larger areas in most cases.

